Regulatory Framework For Major Environmental Programs

Air:

Title V Air Operating Permit: As a major source of Criteria and hazardous air pollutants, as defined in 40 CFR 70, Puget Sound Naval Shipyard will be required to operate under a Title V Permit. This permit is currently being written by the Puget Sound Air Pollution Control Agency. Estimated effective date of this permit is August of 1998.

Opacity: Washington State Administrative Code requires that fugitive air emission sources have less than 20 % opacity at the point of generation. Opacity is the degree of obscuration of an object when viewed through a plume. This requirement applies to the plume created by cutting operations performed outside. (For the purposes of this rule Shipyard dry docks are considered structures which in turn makes the point of generation the, 'lip' of the dry dock.). Newer stationary sources must meet a 5% maximum opacity limit.

To comply with this regulation the Shipyard built two indoor cutting facilities complete with air emission control equipment. These indoor cutting facilities are used for all non-ferrous metals and steel with heavy coatings of paint, adhesive, grease or insulation. In addition, extra caution is used when cutting high. up in a dry dock.

The air pollution control requirements. of the Washington Administrative Code have generally been delegated to local agencies, such as the Puget Sound Air Pollution Control Agency, who then have oversight and enforcement authority.

Toxic Air Contaminants: 29CFR 1910 sub part Z limits the concentration of toxic air contaminants that a worker can be exposed to. Personnel monitoring indicates that permissible contaminate levels for Lead and Arsenic can be exceeded when cutting through steel coated with either copper anti-fouling or lead based paints.

To comply with this regulation the Shipyard implements full lead controls whenever cutting through lead based or copper anti-fouling paints. Full lead controls include air fed hood for the cutters and the establishment of lead work boundaries to keep other workers at a safe distance.

Additionally many registered stationary sources have individual permit conditions unique to a given piece of equipment.

Asbestos:

Regulatory Framework. Asbestos removal operations are regulated by the Puget Sound Air Pollution Control Agency regulation M. In general our asbestos operations are regulated like any other asbestos abatement operation. 'Me operations themselves tend to be unique due to the tight spar-es, the large volume of asbestos, restricted access, and the wide, variety of asbestos materials and components used in the construction of these vessels.

Identification: Prior to. beginning work an asbestos survey is done in the Ship or Building on systems, components, and material that is material".

Submarines that will be going through the recycle program are surveyed before any work is started using the "Naval Methodology" sampling strategy. The asbestos inspectors doing the sampling are trained and certified as Asbestos Hazard Emergency Response Act (AHERA) Building inspectors, per CFR 763 Subpart M, or are under the direction of a AHERA Building Inspector. The Naval Methodology sampling strategy lists the suspect materials that will need to be looked at such as, high temp piping insulation, bulkhead insulation, flooring, etc., and the amount of samples required.

Ships undergoing repair and overhaul are surveyed for asbestos using the AHERA protocol (trained in CFR 763) prior to arrival at the Shipyard. 'Me asbestos inspectors, doing the inspection are trained and certified as AHERA Building inspectors, per CFR 763 Subpart M. The CFR outlines the amount of samples required for TSI, surfacing material and miscellaneous material. The inspectors look at all suspect material and can either take a sample to prove the material is non-asbestos or assume the material is asbestos.

Removal: To remove material that has been identified as asbestos-containing the supervisor and workers involved in will be asbestos qualified and use asbestos controls to work with or remove the ACM.

Controls: 'Me level and type on control required will depend on the type or class of asbestos involved. Examples:

Thermal system insulation (TSI) removal will, require Full Asbestos Training and engineering controls (HEPA vacuum, negative pressure enclosure, glove bag, PPE appropriate for the job). Floor tile removal will require Limited Asbestos Training and engineering controls (HEPA vacuum, critical barriers, PPE appropriate for the job).

Disposal: After removal the asbestos-containing waste material (ACWM) will be double bagged in 6-mil (minimum) blue waste bags. The waste bags will have the following information: Asbestos Supervisor'sname, asbestosworker'sname, phonenumber, project that was workid, date of removal. The bags will be labeled with a "Danger Asbestos" label and the Shipyard's address. The bags will be taken 'to an approved asbestos Dumpster and the dumpster will then be taken to an approved land fill within 10 days from the date of removal.

Hazardous Waste:

Hazardous Waste (HW - Resource, Conservation and Recovery Act (RCRA) and the Washington State Dangerous Waste Regulations): Supplemental controls beyond those required by RCRA have been implemented in environmentally sensitive areas (i.e., Dry Docks, Piers, etc), to provide additional protection to the water of Puget Sound. PSNS has also chosen to internally review and solicit contractors for disposal of HW generated at the facility, including RW from ship recycling. Close review of disposal contracts/contractors is essential to ensure proper treatment/disposal of the unique types and volumes of HW generated from ship recycling. Additionally, the types and volumes of-hazardous wastes generated from ship recycling, as well as which disposal contractor and how that contractor manages-the waste, is reported annually to the Washington State Department of Ecology.

Enforcement of the Resource, Conservation and Recovery Act (RCRA) has been delegated to the Washington State Department of Ecology, and is implemented under Washington Administrative Code 173-303. This Code governs the management of all RCRA Hazardous Wastes as well as Washington State Dangerous and Extremely Hazardous Waste generated at Puget Sound Naval Shipyard. To fully comply with this regulation and to protect workers and the environment, PSNS has taken the following approach to managing Hazardous Waste (this term is used to include Washington State Dangerous and Extremely Hazardous Waste) from ship recycling:

Identification: For each class of ship recycled, PSNS develops a "Common Shipboard Hazardous Materials Matrix" to identify Hazards, potential sources, sampling requirements, and handling requirements of materials encountered during recycling operations. This matrix is used to identify where Hazardous Waste (HW) will be generated, or when to sample to determine if WH will be generated With this information, HW can be properly managed and removed from the ship for temporary storage or accumulation at or near the work site.

Accumulation: Accumulation or Storage of HW is only allowed in designated and registered area in the Shipyard. At the end of each working s@ all RW generated is placed into an accumulation area to ensure that it is properly managed, controlled, and entered into the HW tracking system. Accumulation in Dry Docks, Piers, and other "Over-the-Water" areas may have special controls and. requirements (i.e., secondary containment security, etc.) if the type/form of the waste poses additional risks to the waters of Puget Sound. After sufficient quantities, or after completing the, job, HW is transferred from the Accumulation Areas to the on site Interim Status Storage Facility (RCRA permitted storage facility) for inspection/preparation for shipment off site to the HW disposal contractor.

Disposal: After properly packaging and manifesting, HW is sorted off site by private contractors for treatment and/or disposal. Disposal contractors are carefully reviewed and investigated by PSNS not only from a competitive stand point but also to ensure that they are legitimate, solvent, capable, and permitted to manage our HW. These contracts are reviewed and renewed every I - 3 years.

Tracking: From the point of Accumulation to Final Disposal, PSNS maintains a detail inventory and tracking database of each and every container of HW generated. This information includes an immense amount of data including the type of waste, container, unique bar-code, weight, waste designation, date generated, date disposed, current location, etc. Data from this database is used to generated shipping manifests, annual reports, b@ charges, etc.

Polychlorinated Biphenyl:

Regulatory Frame Work.- The Shipyard's PCB program is regulated by the EPA. Puget Sound Naval Shipyard is recognized by the Navy, DoD and the Environmental Protection Agency as a leader in the control and disposal of Polychlorinated Biphenyl (PCBs). The scope of the Shipyard's PCB program is unparalleled at any Navy facility. The Shipyard has identified many uses of PCB that are unique to the Navy and developed strategies to control and safely dispose of them.

The Shipyard has developed a relationship with the TSCA regulators both at the local and national levels. These relationships have allowed the Navy to have a voice in proposed legislation. The Shipyard was also part of the Environmental Leadership Program where we worked with the local region and permitted the-destruction of PCBS. The purpose of this destruction was to facilitate the study of the off gasses from some of the Navy's unique sources of PCBS. Our in depth knowledge and proactive management of PCBs has earned Puget Sound Naval Shipyard a great deal of respect throughout the regulated community and the Navy.

Water:

Regulatory Frame Work. Federal Facilities in the State of Washington are currently regulated by the EPA for NPDES issues. The NPDES program controls pollutant levels from direct discharges to navigable waters, including dry dock and storm water discharges, via an NPDES permit. The NPDES permit includes discharge limits for pollutants known or of having a high potential for discharge from a given facility. The Washington Department of Ecology has regulatory oversight for Shipyard, discharges to the sanitary sewer.

NPDES Permit Limits: Puget Sound Naval Shipyard's current NPDES permit contains discharge limits from dry dock discharges for Copper and Oil and Grease. Oil and Grease levels have been m the acceptable range since they were put in place at the beginning of this permitting period. In order to comply with the Copper discharge limits the Shipyard spends an estimated 2 million dollars per year removing copper bearing dust from dry dock floors. In addition the Shipyard is in the process of modifying its dry docks to include systems designed to catch and treat, (if necessary), surface water run off.

State Waste Discharge Limits: Puget Sound Naval Shipyard's State Waste Discharge Permit contains limits for discharges from the shipyard to the sanitary sewer. Regulated discharges and their related permit conditions are shown in the table below:

WDOE	NAVY	POLLUTANT	MONTHLY	DAILY	SAMPLING	SAMPLE
SMPL	SAMPLE	PARAMETER	AVERAGE	MAXIMUM	FREQUEN CY	TYPE
POINT	POINT				CI	
NMB R	NUMBER					
1	910-871-001	Building 871 Indu Pretreatment	strial			
		Flow (gpd)	N/A	82000	Each Batch	Dip Stick
		Cadmium(mg/ L)	0.17	0.17	Each Batch	Composite
		Chromium(mg/L)	1.7	2.77	Each Batch	Composite
		Copper(mg/L)	2.07	3.38	Each Batch	Composite
		Lead(mg/L)	0.43	0.69	Each Batch	Composite
		Mercury(mg/L	0.1	0.1	Once/3 Months	Composite
		Nickel(mg/L)	2.38	3.2	Each Batch	Composite
		Silver(mg/L)	0.24	0.43	Each Batch	Composite
		Zinc(mg/L)	1.48	2.61	Each Batch	Composite
		TTO(mg/L)	N/A	2.13	Once/3 Months	Composite
		Tin(mg/L)	N/A	N/A	Once/3 months	Composite
		Cyi3nide(T)(m g/L)	0.6	0.6	Once/3 months	Composite
		PCB's	N/A	5.2	Once/3 months	Composite
2 910-8′	71-002	Building 871 Industri Cyanide	al Pretreatment			
		Flow(gpd)	N/A	30000	Once/3 months	Dip Stick
		Cyanide(mg/L	0.65	1.2	Once/3 months	Grab
3 260-D	D6-001 Bilgewa	ater System at Drydo	ock #6-			
		40GPM	NT/A	42 200	M (1. 1	Marian
		Flow(gpd) Cadmium(mg/	N/A 0.17	43,200 0.17	Monthly N/A	Meter Composite
		L) Chromium(mg	5	5	Monthly	Composite
		/L) Copper(mg/L)	5.2	5.2	Monthly	Composite

Lead(mg/L)	1.3	1.3	Monthly	Composite
Nickel(mg/L)	3.2	3.2	Monthly	Composite
Silver(mg/L)	2	2	N/A	Composite
Zinc(mg/L)	5	5	Monthly	Composite
TTO(mg/L)	2.13	N/A	Once/3	Composite
			Months	
Tin(mg]L)	N/A	N/A	Once/3	Composite
			Months	
TPH(@g/L)(G	N/A	100	Once/3	Grab
&D)			Months	

4 260-DD2-001 Bligewater System W of Drydock #2- 40GPM

Flow(gpd)	N/A	43,200	Monthly	Meter
Cadmium(mg/	0.17	0.17	N/A	Composite
L)				
Chromium(mg	5	5	Monthly	Composite
/L)				
Copper(mg/L)	5.2	5.2	Monthly	Composite
Lead(mg/L)	1.3	1.3	Monthly	Composite
Nickel(mg/L)	3.2	3.2	Monthly	Composite
Silver(mg/L)	2	2	N/A	Composite
Zinc(mg/L)	5	5	Monthly	Composite
TTO(mg/L)	2.13	N/A	Once/3	Composite
-			Months	_
Tin(mg/L)	N/A	N/A	Once/3	Composite
			Months	-
TPH(mg/L)(G	N/A	1 00	Once/3	Grab
&D)			Months	

5 260-DOI-001 BilgevVater System W of Orydock#l - 40GPM

Flow(gpd)	N/A	43,200	Monthly	Meter
Cadmium(mg/	0.17	0.17	N/A	Composite
L)				
Chromium(m	5	5	Monthly	Composite
/L)			•	•
Copper(ing/L)	5.2	5.2	Monthly	Composite
Lead(mg/L)	1.3	1.3	Monthly	Composite
Nickel(mg/L)	3.2	3.2	Monthly	Composite
Silver(mg/L)	2	2	N/A	Composite
Zinc(Tg/L)	5	5	Monthly	Composite
TTO(mg/L)	2.13	N/A	Once/3	Composite
			Months	•
Tin(mg/L)	N/A	N/A	Once/3	Composite
			Months	•
TPH(mg/L)(G	N/A	1 00	Once/3	Grab
&D)			Months	

		FI (1)	NT/A	12 200	3.6		3.6	
		Flow(gpd)	N/A	43,200	Mont	hly	Meter	•
		Cadmium(mg/	0.17	0.17	N/A		Compos	site
		L)	~	-	3.5 .1		C	•.
		Chromium(mg /L)	5	5	Month	ly	Compos	site
		Copper(mg/L)	5.2	5.2	Month	ly	Compos	site
		Lead(mg/L)	1.3	1.3	Month	•	Compos	site
		Nickel(mg/L)	3.2	3.2	Month	•	Compos	
		Silver(mg/L)	2	2	N/A		Compos	
		Zinc(mg/L)	5	5	Mont	nlv	Compos	
		TTO(mg/L)	2.13		N/A	Once/3	Compos	
		110(mg/2)	2.13		1 1/1 1	Months	Compo	5100
		Tin(mg/L)	N/A		N/A	Once/3	Compos	site
		I III(IIIg/L)	14/21		1 1/2 1	Months	Compo	3100
		TPH(mg'/L)(G	N/A		1 00	Once/3	Grah	
		&D)	14/74		1 00	Months	Grao,	
		&D)				Monuis		
7 260-	Pier3-001 Bilger	water System Located a	t Pier 3-					
		1 OOGPM	37/4	06.400		3.6 .1.1		3.5 .
		Flow(gpd)	N/A	86,400		Monthly	/,	Meter
		Cadmium(mg/	0.17	0.17		N/A		Composite
		L)						
		Chromium(mg /L)	5	5		Monthly	7	Composite
		Copper(mg/L)	5.2	5.2		Monthly	1	Composite
		Lead(mg/L)	1.3	1.3		Monthly		Composite
		Nickel(mg/L)	3.2	3.2		Monthly		Composite
		Silver(mg/L)	2	2		N/A		Composite
		Zinc(mg/L)	5	5		Monthly	7	Composite
		TTO(mg/L)	2.13	N/A		Once/3	'	Composite
		TTO(mg/L)	2.13	14/74		Months		Composite
		Tin(ingiL)	N/A	N/A		Once/3		Composite
		Im(mgiL)	IN/A	IN/A		Months		Composite
		TDII(/L)(C	NT/A	1 00				Cont
		TPH(mg/L)(G	N/A	1 00		Once/3		Grab
		&D)				Months		
8	38-58-002	02IN2 System Rinsew	ater TO BUILDI	NG 871 no san	npling r	equiremen	t	
9	38-58-003	Cleaning with Non-Io	nic Detergents					
		Flow(gpd)	N/A	1 000		N/A		N/A
		no sampling requi		1 000		1 1/1 1		1 1/1 1
10	42-107-002 Hy	drotest/Flux Flush Bend	ch& TSP Flux					
		Flush	NT/A	21 000		NT/A		NT/A
		Flow(gpd)	N/A	21 000		N/A		N/A
		Cu	5.2	5.2		once/3		Grab
		701				months		<i>a</i> .
		Pb	1.3	1.3		once/3		Grab
				a	2.2	months		
		note: Testing is. requ		-		only.		

The maximum permitted flow for flux flush is 2000 gpd.

11	56-107-008	B Hose Fl	ush Utility Sink Flow(gpd) no sampling	N/A requirement	60	N/A	N/A
.12	56-107-012	. Hydrote	est Flush Water Flow(gpd) no test no sampling	N/A requirement	30	N/A	N/A
13	56-107-020	Steamcl Pipes	and 12)	From Bent (includes,,@	,v from 56-107-08		
			Flow(gpd) no sampling	N/A requirement	1 000	N/A	N/A
14	56-107-021	High P	ressure Pipe T Stand				
			Flow(gpd)	N/A	50	N/A	N/A
15	57-107-001	Washdo Area	own Deck of Lag	ging Removal			
		Flow(gr PCB(ug		N/A 1 5	2200 15	N/A Once/- 3 months	N/A Grab
			on for PCB's of	or PCB's is 120 microgra 15.0 micrograms per liter			ollowing issuance
16	37-147-001		rgical Sample				
		Grindin Flow(gr no samp		N/A	1	N/A	N/A
17	37-147-002-	Flow(gr	ooling Wastewa od) oling requireme	N/A	500	N/A	N/A
18 1	35-147-001	X-Ray l Rinsewa	Development				
		Flow(gr		N/A	3000	N/A	N/A
				2	2	on a= /2	Cmo.L
		Silver(r		2	2	once/3 months	Grab

The interim limitation for silver is 17.0 milligrams per liter.

The final limitation of 2.0 milligrams per liter shall become effective two years after issuance of this permit.

		Flow(gpd) Lead(mg/L) no sampling	requirement	N/A 1.3		50 1.3	N/A N/A	N/A Grab
20	134-371-004			CH DISCH	IARGE TWICE PE	ER.		
		Bath Flow(gpd)	YEAR	N/A		10	N/A	N/A
		no sampling	requirement			10	1 1/1 1	1,712
21	31-427-0-01	Rotocione Airclea Cutting/Grinding Flow(gpd) no sampling req		c N/A		300	N/A	N/A
22	21 427 002	D	6 34 . 1	/DI				
22	31-427-002 Cutting	Rotocione Airclea	mer for Metal	/Plastic				
	Flow(gr		N	J/A	300		N/A	N/A
	no samp	oling requirement						
23	31-427-003	Plastic Part Cutting Water	Saw Coolant	t/Dust				
		Flow(gpd)		J/A	50		N/A	N/A
		no sampl	ing requireme	ent-				
24	51-427-001	Freedom Kleen Pa Water Flow(gpd) no sampling requ	N/		50		N/A	N/A
25	06/00 421 00	1 Illtraconia Class	on fon					
23	00/99-431-00	1 Ultrasonic Cleane Small Parts	er for					
		Flow(gpd)	N/A	5 N/A	N/A no sampling	g require	ement	
26	06/99-431	-003 Ink Pen Ultra Flow(gpd) no sampling	N/A 5 1	N/A	N/A			
	27 0	6199-431-004 Gauş Flow(gpd) no sampling requi	N/A 65	er N/A	N/A			
28	06/99-431	-005 Tool Product Bucket	ion Quench					
			N/A 5 I irement	N/A	N/A			
29	06/99-431	-006 Pump Repair	and Air Co	nditioning	Washing			
		Operations Flow(gpd) no sampling requi		N/A	N/A			

	Ultrasonic Parts	Cleaning		
001	Tank Flow(gpd)	N/A	40 N/A	N/A
	no sampling	require		17/1
		1		
31 31-431-	Water Jet			
DOORI-002	Cutting Flow(gpd)	N/A	1 000 N/A	N/A
	Chromium(mg	6	5 once/6	Grab
	/L)	Ü	months	
	Nickel(mg/L)	3.2	3.2 once/6 months	Grab
	Zinc(mg/L)	5	5 once/6 months	Grab
	Copper(mg/L)	5.2	5.2 once/6	Grab
			months	
32 31-431@MEZ	Z- Nuclear	Valve	'Cleaning	
003	Flow(gpd)	N/A	120 N/A	N/A
	1 low(gpu)	11/11	120 IVA	IVA
	no sampling re	quiremen	ıt	
33 31-431-004 V	alve Test Closed	Loons		
33 31 431 004 v	Flow(gpd)	N/A	50 N/A	N/A
	no sampling re	quiremen	ıt	
34 41-431-001	Doilor Foodyyata	. Tuootuo	ont Westervister on	d Dlawdown/Condonasta
34 41-431-001	Flow(gpd),		ant wastewater and 8000 N/A	d Blowdown/Condensate N/A
	no sampling requ		00001771	17/11
35 67-431-407 002	'A- Circuit Board	Rinse PR TCA	OCESS CHANG	ES NO LONGER USE
	Flow(gpd)	N/A	30 N/A	NIA
	Lead(mg/L)	1.3	1.3 N/A	N/A
	no sampling req	uirement		
36 67-431-408 003	88- Photo Darkro	om Disc	charge	
	Flow(gpd)	N/A	50@ N/A	N/A
	Silver(mg/L)	2	2 N/A	N/A
The inte	orim limitation for	cilvar ic	1 7.0 milligrams p	oor liter
				become effective two years after issuance
of this r		8	1	y

37 67-431-414B- Electronic Cabinet

no sampling requirement

004 Washdown

of this permit.

 $\begin{array}{cccc} Flow(gpd) \ N/A & 200 & N/A & N/A \\ & no \ sampling \ requirement \end{array}$

38 67-431-510- Circuit Board Dish

005 Washers

Flow(gpd) N/A 200 N/A N/A Lead(mg/L) 1.3 1.3 N/A N/A

no sampling requirement

39 67-431-GAUGE Gauge Cleaning Sink

ROOM-006 Flow(gpd) N/A 40 N/A N/A

no sampling requirement

40 135-431-203- Photo Developer Parts

001 Cleaning

Flow(gpd) N/A 40 N/A N/A

no sampling requirement

41 135-431-203- X-Ray Developer Rinse

002

months

The interim limitation for silver is 17.0 milligrams per liter.

The final limitation of 2.0 milligrams per liter she((become effective two years after issuance of this permit.

42 51-435-001 Braze Flux Wash Sink

Flow(gpd) N/A 20 N/A N/A no sampling requirement

43 1113-435-001 Shipyard Cafeteria Sinks

Flow(gpd) N/A 2200 N/A N/A no sampling requirement

44 1113-435-002 Shipyard Cafeteria Commercial INCLUDED IN CAFETERIA SINK FLOW

Washer ABOVE

Flow/(gpd) N/A FLOW INCLUDED IN 1113-435-

001

no sampling requirement

45 820-437-001 Auto Parts Washing

Flow(gpd) N/A 200 N/A N/A no sampling requirement

46 06/99-431-002 High Pressure Hose

Flushing -

Flow(gpd) N/A 12 N/A N/A no sampling requirement

47 06-452-001 Respirator/Apparel/Face Shield Wash

		Flow(gpd)	N/A	600 N/A	N/A no sampling requirement
48	06-452-002	High Pressure He Flushing Flow(gpd) no sampling re	N/A	20 N/A	N/A
49	37-452-001	Flow(gpd) no sampling		00 N/A	N/A
60	37-452-002	Non contact Furnace Fans Flow(gpd)	Cooling W	Vater for 0000 N/A	N/A
no	sampling re	equirement			
51	02-455-001	Mechanical Car	Wash		
		Flow(gpd) no sampling		200 N/A	N/A.
52	02-455-004	H6nd Car Wash Flow(gpd) no sampling	N/A 60 requireme	00 N/A ent	N/A
53	98-455-001	Crane Parts Cleaning Flow(gpd) no -sampling	Steam N/A 40 requirement	000 N/A	N/A
54	57-457-001	Lagging Cement Flow(gpd) no sampling rec	N/A 60	0 N/A	N/A
55 1	71-457-001	Titanium/SS/Mo Quench Tank Flow(gpd) no sampling requ	N/A	90 N/A	N/A
56	71-457-002	Varnish Room Be Flow(gpd) no sampling rec	N/A	20 N/A	N/A

		Cutoff Saw Flow(gpd) no sampling	N/A requirer	50 nent	N/A		N/A
58	71-457-004	Silk Screen Flow(gpd) no sampling	Washing N/A requirer	1 00	N/A	N/A	
59	26-460-001	Gas Hose Leak To Flow(gpd) no sampling req	N/A	10	N/A	N/A	
60 (06/99-462-00	1 Regulator/Hose	Test Ste	eam			
		Condensate Flow(gpd) no sampling req	N/A	1 00	N/A	NIA	
61 (06/99-462-002	2 Braze Quench Si Flow(gpd) no sampling req	N/A	1 00	N/A	N/A	
62 (06/99-462-003	3 Plumbing Valve Flow(gpd) no sampling req	N/A		gh N/A	N/A	
63	06/99-462-0	004 High Pressure	Hose Tes	t /Steriliz	ze		
		Trough Flow(gpd) no sampling req	N/	400	N/A	N/A	
64	06/99-462-0	005 Grade A Pure	Water Ho	se			
		Washing Flow(gpd) no sampling'req	N/A uirement	400	N/A	N/A	
65	06/99-462-0	006 HP Air Compr	essor Filt	er Ultras	onic		
		Cleaning Flow(gpd) no sampling req	N/A	10	N/A		N/A
66	67-466-001 I	Electronic Parts Ri Flow(gpd) no sampling req	N/A	5	N/A		N/A

67	37-469-001 Propeller Dye Penetrant Testing Flow(gpd) N/A 75 N/A no sampling requirement	N/A
68 06-495	5-001 Welding- Equipment Filter Ultrasonic Cleaning Flow(gpd) N/A 50 N/A no sampling requirement	N/A
69 67-500	O-001 Sonar Cleaning Soak Tank Flow(gpd) N/A 1 00 N/A no sampling requirement	N/A
70 67-50	0-002 Sonar Hydratest Tank Flow(gpd) N/A 600 N/A no sampling requirement	N/A
71 500-	502-001 Industrial Clothes Washers Flow(gpd) N/A 1 1 000 no sampling requirement	N/A N/A
72 500-	502-002 Developer from Noritsu Developing Machine Flow(gpd) N/A 10 N/A no sampling requirement	N/A
73 500-	502-003 Fixer from Noritsu Developing Machine Flow(gpd) N/A 10 N/A no sampling requirement	N/A
.74 820-	502-001 Cafeteria Automatic Dishwasher Flow(gpd) N/A 600 N/A no sampling requirement	N/A
75 820-	Sink Flow(gpd) N/A N/A N/A no sampling Fourierment	N/A
76 820-	502-005 Latex Paint Brush Cleaning. Sink Flow(god) N/A 200 N/A no sampling requirement	N/A

77 NDC-506-001 X-Ray Film Developer

Flow(gpd) N/A 1 00 N/A N/A Sitver(mg/L) 2 2 N/A N/A

The interim limitation for silver is 17.0 milligrams per liter.

The final limitation of 2.0'milligrams per liter shall become effective two years after issuance of this permit. no sampling requirement

78 1326-530-001 Reprolith Developer RINSEWATER & FIXER/DEVELOPER

SEPARATE

Flow(gpd) 50 N/A N/A Silver(mg/L) 2 2 N/A N/A

The interim -limitation for silver is 17.0 milligrams per liter.

The final limitation of 2.0 milligrams per liter shall become effective two years after issuance of this permit.

no sampling requirement

79 1326-530-002 Varityper Developer R(NSEWATER & FIXER/DEVELOPER

SEPARATE

Flow(gpd)	N/A	50	N/A	N/A
Silver(mg/L)	2	2	N/A	N/A
Copper(mg/L)	5.2	5.2	N/A	N/A
Zinc(mg/L)	5	5	N/A	N/A

The interim limitation for silver is 17.0 milligrams per liter.

The final limitation of

2.0 milligrams per liter shall become effective two years after issuance of this permit.

no sampling requirement

80 953-818-001 Air Compressor Heat

Exchanger

81 1385-850-207- Photoprocessing Machines

003

Flow(gpd) N/A 1 N/A N/A Silver(mg/L) 2 2 N/A N/A

The interim limitation for silver is 17.0 milligrams per liter.

The final limitation of 2.0 milligrams per liter shall become effective two years after issuance of this permit. no sampling requirement

82 203-85OA-001 Film

Processor

Flow(gpd) N/A 1 00 N/A N/A Silver(mg/L) 2 2 N/A N/A

The interim limitation for silver is 17.0 milligrams per liter.

The final limitation of 2.0 milligrams per liter shall become effective two years after issuance of this permit.

no sampling requirement

83 203'85OA-002 Color Paper Developer

Flow(gpd). N/A 1200 N/A N/A Silverfmg/L) 2 2 once/6 Grab months

The interim limitation for silver is 17.0 milligrams per liter.

The final limitation of 2.0 milligrams per liter shall become effective two years after issuance of this permit.

84 203-85OA-003 Black and White Developer

Flow(gpd) N/A 250 N/A N/A Silver(mg/L) 2 2 N/A N/A

The interim limitation for silver is 17.0 milligrams per liter.

The final limitation of 2.0 milligrams per liter shall become effective two years after issuance of this permit.

no sampling requirement

85 203-85OA-004 Color Paper Developer

Flow(gpd) N/A 1200 N/A N/A Silver(mg/L) 2 2 once/6 Grab months

The interim limitation for silver-is 17.0 milligrams per liter. The final limitation of 2.0 milligrams per liter shall- become effective two years after issuance of this permit.

86 56-856-001 Pipe/Pump Test Sump

Flow(gpd) N/A 100 N/A N/A no sampling requirement

87 90-856-001 Braze Flux

Flush 1 800 N/A N/A Flow(gpd) N/A Copper(mg/L) 51.2 5.2 once/6 Grab months Chromium(mg 5 5 once/6 Grab months Lead(mg/L) Grab 1.3 1.3 once/6 months Nickel(mg/L) Grab. 3.2 3.2 once/6 months

	Zinc(mg/L)	5	5		once/6 months	Grab
88 90-856-002	TSP Pipe Cleanin Rinsewater	ng N/A	2000		N/A	N/A
	Flow(gpd) Copper(mg/L)	5.2	5.2		once/6 months	Grab
	Chromium(mg /L)	5	5		once/6 months	Grab
	Lead(mg/L)	1.3	1.3		once/6 months	Grab
	Nic.kel(mg/L)	3.2	3.2		once/6 months	Grab
	Zinc(mg/L)	5	5		once/6 months	Grab
89 90	0-856-003Ultrasor Flow(gpd) no sampling r	N/A	20	r	N/A	N/A
90 17-857-001	Aluminum Passiv as haz waste no sampling requ		akite Deg	reaser		
91 17-867-002	2Passivation Ho	t Water	·.			
	Rinse	NT/A		600	NT/A	NT/A
	Flow(gpd) Cadmium(mg/	N/A 0.17		600 0. 1 7	N/A once/3	N/A Grab
	L)	0.17		0.17	months	Grao
	Chromium(mg	1.71		2.77	once/3 months	Grab
	Copper(mg/L)	2.07		3.38	once/3 months	Grab
	Lead(mg/.L)	0.43		0.69	once/3 months	Grab
	Nickel(mg/L)	2.38		3.2	once/3 months	Grab
	Zinc(mg/L)	1.48		2.67	once/3 months	Grab
	TTO(mg/L)	N/A		2.13	N/A	Grab
	Cyanide(T)	0.6		0.6	once/3 months	Grab

note: TTO certification statement required.in lieu of sampling for TTO

92	17-857-007	Passivation	Hot	Water

Rinse				
Flow(gpd)	N/A	600	N/A	N/A
Cadmium(mg/	0. 1'7	0.17	once/3	Grab
L)			months	
Chromium(mg	1.71	2.77	once/3	Grab
/L)			months	
Copper(mg/L)	2.07	3.38	once/3	Grab
			months	
Lead(mg/.L)	0.43	0.69	once/3	Grab
			months	
Nickel(mg/L)	2.38	3.2	once/3	Grab
			months	
Zine(mg/L)	1.48	2.67	once/3	Grab
			months	
TTO(mg/L)	N/A	2.13	once/3	Grab
			months	
Cyanide(T)(m 0	.6	0.6	once/3	Grab
g/L)			months	

note: TTO certification statement required in lieu of testing for

TTO

93 1 7-857-010 Photographic Development Baths

Rinsewater

Flow(gpd) N/A 100 N/A N/A Silver(mg/L) 2 2 N/A N/A

The interim limitation for silver is 17.0 milligrams per liter.

The final limitation of 2.0 milligrams per liter shall become effective two years after issuance of this permit.

no sampling requirement

94 ROTO-1 7-857@ Rotoclone, East Side Building 857-

001 Photo related

 $Flow(gpd) \hspace{1cm} N/A \hspace{1cm} 3000 \hspace{1cm} N/A \hspace{1cm} N/A \hspace{1cm} no \hspace{1cm} sampling \hspace{1cm} requirement$

95 ROTO-1 7-857- Rotoclone-West Side of Building 857-acid/base

002 related

Flow(gpd) N/A 3000 N/A N/A no sampling requirement

96 ROTO-1 7-857- RotoclonerWest Side of Building 857

003

Flow(gpd) N/A 3000 N/A N/A no sampling requirement

97 820-864-001 Food Service Automatic Dishwasher

Flow(gpd) N/A 1 000 N/A N/A no sampling requirement

98	800,865-001	Washers Flow(gpd)	N/A require	1 1 000 ement	N/A	N/A
99	815-866-001	Food Grinder Flow(gpd) no sampling red	N/A quiremen	200 t	N/A	N/A
100	815-866-0	02 Mass Hall Indu Dishwasher Flow(gpd) no sampling req	N/A	:	N/A	N/A
101	71-873-00	1 Steam Condens: Flow(gpd) no sampling	N/A	20	N/A	N/A
102	71-873-00	2 Buffer/I Flow(gpd)	Bandsaw N/A	Rotocione 50	N/A	N/A
103	03-874-00	1 Paper Shredder Water Flow(gpd) no sampling req	N/A	200	N/A	N/A
104	03-874-00	2 Hazardo Rainwater Flow(gpd) TTO(mg/L)	ous Waste N/A N/A	e Tank Area 6000 2.13	N/A once/6 month	N/A Grab is
10.5		3 Drum Storage Stormwater Flow(gpd) no sampling req	N/A	2000	N/A	N/A
106	99-875-00	1 Sewage/CHT H Cleaning Flow(gpd). no sampling req	N/ A	1 0000	N/A	N/A
107	99-875-00	2 Hose Pressurcr Manifold Flow(gpd)	Test N/A	15000	N/A	N/A

no sampling requirement

108	57-879-00	1 Lagging Cemen Flow(gpd) no sampling requ	N/A	eanin	g Sink 50	N/A	N/A
109 8	00-885-001	Industrial Clothe Flow(gpd) no sampling req	N/A	830	0	N/A	N/A
110 5	7-893-001 (Cement Lagging T Cleaning Flow(gpd) no sampling req	N/A	50	N/A	N/A	
111 9	92-900-001	Air Compressor (Slowdown Flow(gpd) Copper(mg/L)	Cooling T N/A		N/A	N/A	
112 9	92-900-002	Diesel Generator Slowdown Flow(gpd) Zinc(mg/L) Copper(mg/L) no sampling req	N/A 5 5.2	5000	er O N/A 5 N/A .2 N/A	N/A N/A. N/A	
113 9	53-923-001	Air Compressor Water Flow(gpd) Zinc(mg/L) Copper(mg/L) no sampling req	N/A 5 5.2	350 5 5.2	N/A N/A N/A	N/A N/A N/A	
114	063-940-L. 001	AB- Coulter Blood Flow(gpd) no sampling requ	N/A	ounte		N/A	
115	063-940-2 001	Hydroco Flow(gpd) no sampling req	ollator N/A uirement	5 N	ilization J/A	N/A	
116	063-940-2	13- Small H Steriliza Flow(gpd) no sampling req	N/A	tor 1 N	V/A	N/A	

117 063-940-213- Physical Therapy Whirlpool Cleaning

003

Flow(gpd) N/A 50 N/A N/A no sampling requirement

118 063-940-213- X-Ray Film Processor

004

The interim limitation for silver is 1 7.0 milligrams per liter.

The final limitation of 2.0 milligrams per liter shall become effective two years after issuance of this permit.

119 800-942-001 Industrial Clothes Washers

Flow(gpd) N/A 8300 N/A N/A no sampling requirement

120 03-944-001

Rainwater N/A 13,000 N/A N/A Sumps PCB(ug/L) 15 15 once/3 Grab months

The interim limitation for PCB's is 120 micrograms per liter. The final limitation for PCB's of 15.0 micrograms per liter shall become effective two years following issuance of this permit.

121 350-WERF-001 Metal Cutting Cooling Water-normaly discharge through bilge

water treatment

Flow(gpd) 5000 N/A N/A N/A Cadmium(mg/ 0.17 monthly 0.17 Batch-grab L) Copper(mg/L) 5.2 monthly Batch-grab 5.2 Chromium(mg Batch-grab 5 monthly 5 /L) Nickel(mg/L) 3.2 3.2 monthly Batch-grab test only if not treated and not sent to Building 871

122 03-7133-001 Gas Fired

Boiler

Flow(gpd) N-/A 500 N/A N/A no sampling requirement

123 03-138-001 Gas Fired

Boiler

Flow(gpd) N/A 500 N/A N/A no sampling requirement

124 03-192-00	01 Gas Fired Boiler Flow(gpd) no sampling requ	N/A iirement	500	N/A	N/A
125 03-377-001	Gas Fired Boiler Flow(gpd) no sampling	N/A requirer	500 N/. nent	A	N/A
126 03-413-001	Gas Fired Boiler Flow(gpd) no sampling	N/A requirer	500 N nent	/A	N//A
127 03-468-001	Gas Fired Boiler Flow(gpd) no sampling requ	N/A irement	500 N/	A	N/A
128 08-477-001-	Gas Fired Boiler Flow(gpd) no sampling	N/A requirer	500 N/. nent	A	N/A
129 03-551-001	Gas Fired Boiler Flow(gpd) no sampling	N/A requirer	500 N/.	A	N/A
130 03-615-001 no sampling requ	Boiler Flow(gpd)	N/A	500 N/	A	N/A
131 03-618-001	Gas Fired Boiler Flow(gpd) no sampling	N/A requirer	500 N/.	A	N/A
132 03-621-001	Gas Fired Boiler Flow(gpd) no sampling	N/A requirer	500 N/.	A	N/A
	Boiler Flow(gpd)	N/A	500 N	'A	N/A
134 03-624-001		N/A requirer	500 N/. nent	A	N/A

135 03-6 Boiler	626-001	Gas Fi	red				
	Flow(gr no samp		N/A requires	500 N/Ament	A	N/A	
136 03-6	628-001	Gas Fi Boiler Flow(gr no samp	od)	N/A requirer	500 N/.	A	N/A
137 03-0	631-obi	Gas Fi Boiler Flow(gr no samp	od)	N/A requirer	500 N/.	A	N/A
		Gas Fi Boiler Flow(gr		N/A	500 N/.	A	N/A
no samp	oling requ	mement					
139 03-0	635-001	Gas Fi Boiler Flow(gr no samp	od)	N/A requirer	500 N/.	A	N/A
140 03-0	637-001	Gas Fi Boiler Flow(gr no samp	od)	N/A requirer	500 N/.	A	N/A
141 03-0	639-001	Gas Fi	red				
Flow(gp	od)	Boiler N/A No sam	500 N pling req	N/A uirement	N/A		
142 03-6	640-001	Gas Fi Boiler Flow(gr no samp	od)	N/A requirer	500 N/. ment	A	N/A
143 03-0	541-001	Gas Fi Boiler Flow(gr no samp			500 N/.	A	N/A
144 03-0	542-001	Boiler Flow(gr		N/A irement	500 N/	A	N/A
145 03-6	644-001	Gas Fi Boiler Flow(gr no samp		N/A requirer	500 N/. ment	A	N/A
146 03-0	646-001	Gas Fir	red				

	Boiler Flow(gpd) no sampling	N/A requirer	500 N nent	I/A	N/A
147 03-648-001	Gas Fired Boiler Flow(gpd) no sampling	N/A requirer	500 N nent	//A	N/A
148 03-649-001 no sampling requ	Boiler Flow(gpd)	N/A	500 N	[/A	N/A
149 03-651-001	Gas Fired Boiler Flow(gpd) no sampling	N/A requirer	500 N nent	//A	N/A
150 03-652-001	Gas Fired Boiler Flow(gpd) no sampling	N/A requirer	500 N nent	//A	N/A
151 03-654-001 Flow(gpd) no samp	Gas Fired Boiler N/A 500 N/A ling requirement	A	N/A		
152 03-656-001	Gas Fired Boiler Flow(gpd) no sampling	N/A requirer	500 N nent	//A	N/A
153 03-658-001	Gas Fired Boiler Flow(gpd) no sampling	NA requirer		//A	N/A
154 03-864-001	Gas Fired Boiler Flow(gpd) no sampling requ	N/A airement	500 N	[/A	N/A
155 03-502-001	Gas Fired Boiler Flow(gpd) no sampling	N/A requirer	500 N nent	I/A	N/A
156 03-865-001	Gas Fired Boiler Flow(gpd)	N/A	500	N/A	N/A

no sampling requirement

157	03-400-00	01 Boiler	Gas	Fired				
		Flow(gp					N/A	N/A
168	03-530-00		Gas	Fired				
		Boiler Flow(gp no sam					N/A	N/A
159	03-466-00	01 Boiler	Gas	Fired				
							N/A	N/A
160	0 3-853-	-001 Boiler	Gas	Fired				
			od) pling	N/A	A equire	500 ement	N/A	N/A
161	03-434-00	01 Boiler	Gas	Fired				
							N/A	N/A
162	03-644-00	01 Boiler	Gas	Fired				
			pd) pling	N/A	A equire	500 ement	N/A	N/A
163 03	-866-1-00	l Boiler	Gas	Fired				
							N/A	N/A
164 03	-866-2-00	1. Boiler	Gas	Fired				
							N/A	N/A
165	03-885-00	01 Boiler	Gas	Fired				
		Flow(gp		N/A		500 ement	N/A	N/A
166'03	-658-001	Gas Fi Boiler	ired					
		Flow(gp		N/A		500 ent	N/A	N/A
167	99-001;00	01 Specia N/A					-	
Flow(g Chrom	gpa) ium(mg	N/A 5		each			composi	ite

Copper(mg/L)	5.2	5.2 each -batch	composite
Lead(mg/L)	1.3	1.3 each batch	composite
Nickel(mg/L)	3.2	3.2 each batch	composite
Zinc(rog/)	5	5 each batch	composite

1-68 99-DD2-Flow(gpd) ChromiLim(mg	001 Spec N/A 5	ial, Hull Treatment at Dr 4000 each batch 5 each batch	ydock 2 meter composite
Copper(mg/L) Lead(mg/L) Nickel(mg/L) Zinc(mg/)	5.2 1.3 3.2 5	5.2 each batch 1.3 each batch 3.2 each batch 5 each batch	composite composite composite
169 99DD3-G Flow(gpd) Chromium(mg /L) Copper(mg/L) Lead(mg/L) Nickei(mg/L) Zinc(mg/)	001 Spec N/A 5 5.2 1.3 3.2 5	ial Hull Treatment at Dry 4000 each batch 5 each batch 5.2 each batch 1.3 each batch 3.2 each batch 5 each batch	wdock 3 meter composite composite composite composite composite
170 99-DD4-0 Flow(gpd) Chromium(mg /L) Copper(mg/L) Lead(mg/L) Nickel(mg/L) Zinc(mg/)	001 Spec N/A 5 5.2 1.3 3.2 5	ial Hull Treatment at Dry 4000 each batch 5 each batch 5.2 each-batch 1.3 each batch 3.2 each batch 5 each batch	ydock 4 meter composite composite composite composite composite
171 99-DD5-001 Flow(gpd) Chromium(mg /L) Copper(mg/L) Lead(mg/L)- Nickel(mg/L) Zinc(mg/)	Special N/A 5 5.2 1.3 3.2 5	Hull Treatment at Drydo 4000 each batch 5 each batch 5.2 each batch 1.3 each batch 3.2 each batch 5 each batch	ck 5 meter composite composite composite composite composite

Flow(gpd)	N/A	4000 each batch	meter
Chromium(mg	5	5 each batch	composite
Copper(mg/L) Lead(mg/L) Nickel(mg/L) Zinc(mg/)	5.2 1.3 3.2 5	5.2 each batch 1.3 each batch 3.2 each batch 5 each batch	composite composite composite

173 71-ODI-0	05 Hydrobla	ast/Pressure Wash V	Water from
Drydock 1			
Flow(gpd)	N/A	30,000 meter	meter
Chromium(mg	5	5 quarterly	composite
/L)			
Copper(mg/L)	5.2	5.2 quarterly	composite
Lead(mg/L)	1.3	1.3 quarterly	composite
Nickel(mg/L)	3.2	3.2 quarterly	composite
Zinc(mg/)	5	5 quarterly	composite

174 71-DD2-005 Hydroblast/Pressure Wash Water from Drydock 2 Flow(gpd) N/A 30,000 meter meter Chromium(mg 5 5 quarterly composite /L)Copper(mg/L) 5.2 5.2 quarterly composite 1.3 Lead(mg/L) 1.3 quarterly composite Nicket(mg/L) 3.2 3.2 quarterly composite 5 Zinc(mg/) 5 quarterly, composite

175 71-DD3-005 Hydroblast/Pressure Wash Water from Drydock 3 Flow(gpd) N/A1 30,000 meter meter Chromium(mg 5 5 quarterly composite /L)Copper(mg/L) 5.2 composite 5.2 quarterly Lead(mg/L) 1.3 1.3 quarterly composite Nickel(mg/L) 3.2, 3.2 quarterly composite 5 5 quarterly Zinc(mg/) composite

176 71-DD4-005

Hydroblast/Press	sure Wash	Water from	
Drydock 4			
Flow(gpd)	N/A	30,000 meter	meter
Chromium(mg	5	5 quarterly	composite
/L)			
Copper(mg/L)	5.2	5.2 quarterly	composite

	Lead(mg/L) Nickel(mg/L) Zinc(mg/)	1.3 5.2 5	1.3 quarterly5.2 quarterly5 quarterly	composite composite
177 71-DD5	-005 Hydroblast/P Drydock	ressure 5	Wash Water from	
	Flow(gpd)	N/A	30,000 meter	meter
		1N/A 5		
	Chromium(mg	3	5 quarterly	composite
	Copper(mg/L)	5.2	5.2 quarterly	composite
	Lead(mg/L)	1.3	1.3 quarterly	composite
	Nickel(mg/L)	3.2	3.2 quarterly	composite
	Zinc(mg/)	5	5 quarterly	composite
1 78 71 -DD6	-005 Hydroblast/P Dryd.ock 6	ressure	Wash Water from	
	Flow(gpd)	N/A	30,000 meter	meter
	ChrGmium(rng	5	5 quarterly	composite
	Copper(mg/L)	5.2	5.2 quarterly	composite
	Lead(mg/L)	1.3	1.3 quarterly	composite
	Nickel(mg/L)	3.2	3.2 quarterly	composite
	Zinc(mg/)	5	5 quarterly	composite
179 57-DD3	-001 Asbestos/PC Flow(gp		ng Removal Area Dec N/A N/A N/A	ek Drain

The interim limitation for PCB's is 120 micrograms per liter. The final limitation for PCB's $\,$

15 quarterly-

of 5.2 micrograms per liter shall become effective two years following issuance of this permit.

composite

180 03-DDI-002 Drydock 1;.Stormwater Collection

PCB(ug/L)

System Flow(god) N/A 42,000 meter meter Chromium(mg 5 quarterly 5 grab 5.2 quarterly Copper(mg/L) 5.2 grab 1.3 quarterly grab Lead(mg/L) 1.3 grab Nickel(mg/L) 3.2 3.2 quarterly Zinc(mg/) 5 5 quarterly grab

1 5

181 03-OD2-002 Drydock 2-Storrnwater Collection

System			
Flow(gpd)	N/A	42,000 meter	meter
Chromium(mg	5	5 quarterly	grab
/L)			
Copper(mg/L)	5.2	5.2 quarterly	grab
Lead(mg/L)	1.3	1.3 quarterly	grab
Nickel(mg/L)	3.2	3.2 quarterly	gre

		Zinc(mg	g/)	5	5 q	uarterly	grab
182	03-DD3	-002 Dry System	dock 3	S-Stormw	ater	Collection	
		Flow(gr Chromit /L)		N/A 5		000 meter uarterly	
		Copper(Lead(m	ng/L)	1.3.	1 .3 3.2	quarterly quarterly quarterly uarterly	grab grab
183	03-DD4		dock 4	-Stormw	ater	Collection	
		System Flow(gr	od)	N/A	42.0	00 meter	meter
			um(mg	5		uarterly	
		Copper(mg/L)	5.2		quarterly	
			g/L)			quarterly	
		,	ng/L)			quarterly	
		Zinc(mg	g/)	5	5 q	uarterly	grab
184	03-DD5		dock 5	5-Stormw	ater	Collection	
Flow(gr	nd)	System N/A	42,000	meter	mete	ar	
	um(mg			terly	grab		
Copper	(mg/L)	5.2	5.2 qu	arterly	grab		
	g/L)		1.3 qu	arterly	grab		
	mg/L)			arterly.			
Zinc(mg	g/)	5	5 quart	terly	grab		
185	03-006- System	002 Oryd	ock 6-	Stormwa	ter	Collection	
Flow(gr	-	N/A	42,000	meter	mete	er	
Chro@i	ium(mg						
/L)	(/T)	<i>5</i> 2	<i>5</i> 0				
Copper		5.2	5.2 qua		grab		
Lead(m Nickel(1.3 3.2	1.5 qu	arterly arterly	grab		
Zinc(m	•	5.2	5.2 qu		gra		
Zincing	51)	3	5 quar	crry	gra		
186	41-PIERS 001	SIDE- Ph	osphate	Boiler	Clean	ning Rinse	water
		Flow(gr		N/A		00 N/A	N/A
			units)	N/A	mini	mum 1/bat	ch grab
		5.0 Chromi	um(mg	5	5 1 /	batch	grab
1 87 CI	D-IR1 -00				g at	Installatio	n
		Restorat Flow(gr	tion Site (od)	001 N/A	25,0	00 1/20,000	meter/tank

		gal	
Lead(mg/L)	1.3	1.3 1/20,000 grab	
		gal	
Nickel(mg/L)	3.2	3.2 1/20,000 grab	
		gal	
Zine(mg/L)	5	5 1-/20,000 grab	
		gal	
TTO's(mg/L)	2.13	2.13 1/20,000 grab)
		gal	

Numbers appearing in the limitations column for this IR site are not limitations, but rather action levels. Whenever an action level is exceeded the shipyard shall inform the Department in writing within one week of becoming aware of such exceedance, and shall briefly describe its plans for preventing such exceedences in the future. IR sampling results shall not be reported on monthly OMRs, but rather, in an annual report to the Department due March 1 5 of each year.

1 88 CD-IR3-001 Construction De-watering at Installation

Restoration Site	003		
Flow(gpd)	N/A	25,000 1/20,000	meter/tank
		gal	
Lead(mg/L)	1.3	1.3 1/20,000 grab	
		gal	
Nickel(mg/L)	3.2	3.2 1/20,000 grab	
_		gal	
Zinc(mg/L)	5	5 1/20,000 grab	
-		gal	
TTO's(mg/L)	2'.13	2.13 1/20,000 grab	
_		gal	

Numbers appearing in the limitations column for this IR site are not limitations, but rather action levels., Whenever an action level is exceeded the shipyard shall inform the Department in writing within one week of becoming aware of such exceedance, and shall briefly describe its plans for preventing such exceedances in the future. IR sampling results shall not be reported on monthly DMRs, but rather, in an annual report to this Department due March 1 5 of each year.

189 CD-IR7-001 Construction Dewatering at Installation

Restoration Site	1			
Flow(gpd)	N/A	25,000	1/20,000	meter/tank
gal		,	•	
Lead(mg/L)	1.3	1.3 1	/20,000	grab
			gal	
Nickel(mg/L)	3.2	3.2	1/20,000	grab
			gal	
Zinc(mg/L)	5	5	1/20,000	grab
			gal	
TTO's(mg/L)	2.13	2.13	1/20,000	grab
			gal	

Numbers appearing in the limitations column for this IR site are not limitations, but rather action levels.. Whenever an action level is exceeded the shipyard shall inform the Department in writing within one week of becoming aware of such exceedance, and shall briefly describe its plans for preventing such exceedances in the future. IR sampling, results shall not be reported on monthly DMRs, but rather, in an annual report to the Department due March 1 5 of each year.

Restor6tion Si	te 8	_		
Flow(gpd)	N/A	25,000	1/20,000	mete
			gal	

190 CD-IR8-001 Construction Dewatering at Installation

Flow(gpd)	N/A	25,000	1/20,000	meter/tank
			gal	
Lead(mg/L)	1.3	1.3	1/20,000	grab
Nielsel(ma/L)	3.2	3.	gal 1/20,000	arch
Nickel(mg/L)	3.2	3.	1/20,000 gal	grab
Zinc(mg/L)	5	5	1/20,000	grab
			gal	
TTO's(mg/L)	2.13	2.13	1/20,000	grab
			gal	

Numbers appearing in the limitations column for this IR site are not limitations, but rather action levels. Whenever an action level is exceeded the-shipyard shall inform the Department in writing within one week of becoming aware of such exceedance, and shall briefly describe its plans for not be reported on monthly DMRs, but preventing such exceedances in the future. IR sampling results shall rather, in an annual report to the Department due March 15 of each year.

191 CD-IR9-001 Construction Dewatering at Installation

Restoration Site	9		
Flow(gpd)	N/A	25,000 1/20,000	meterltank
		gallon	
Lead(mg/L)	1.3	1.3 1/20,000	grab
		gallon	-
Nickei(mg/L)	3.2	3.2 1/20,000	grab
		gallon	
Zinc(mg/L)	5	5 1/20,000	grab
		gallon	
TTO's(mg/L)	2.13	2.1 3 1/20,000	grab
		gallon	

note: sampling is not required if less than 1 000 gpd or 1 0,000 gallons per project Numbers appearing in the limitations column for this IR site are not limitations, but rather action levels.

Whenever, an action level is exceeded the shipyard shall inform the Department in writing within one week of becoming aware of such exceedance, and shall briefly describe its plans for preventing such exceedances in the future. IR sampling results shall not be reported an monthly DMRs, but rather, in an annual report to the Department due March 1 5 of each year.

102 CD ID10C 001	Construction	Darriotanina at	Installation	Doctoration Cita 10	\mathbf{C}
192 CD-IRIOC-001	Construction	Dewatering at	installation	Restoration Site 10	J.C.

Flow(gpd)	N/A	25,000	1/20,000	meter/tank
			gallon	
Lead(mg/L)	1.3	1.3	1/20,000	grab
			gallon	
Nickei(mg/L)	3.2	3.2	1/20,000	grab
			gallon	
Zinc(mg/L)	5	5	1/20,000	grab
			gallon	
TTO's(mg/L)	2.13	2.13	1/20,000 grab)
			gallon	

note:sampling is not required if less than 1000 gpd or 10,000 gallons per project Numbers appearing in the limitations column for this IR site are not limitations, but rather action levels. Whenever an action level is exceeded the shipyard shall inform the Department.in writing within one week of becoming aware of such exceedance, and shall briefly describe its plans for preventing such exceedances in the future. IR sampling results shall not be reported on monthly DMRs,but rather, in an annual report to the Department due March 15 of each year.

193 CD-IRIOE-0	001 Cons	truction Dewate	ering at Installation
Restoration Site	10E		
Flow(gpd)	N/A	25,000 1/20,0	000. meter/tank
		gallon	
Lead(mg/L)	1.3	1.3 1/20,000	grab
		gallon	
Nickel(mg/L)	3.2,	3.2 1/20,000	grab
		gallon	
Zinc(mg/L)	5	5 1/20,000	grab
		gallon	
TTO's(mg/L)	N/A	2.13 1/20,000	O grab
			gallon

note: sampling is not required if less than 1000 gpd or 10,000 gallons per project Numbers appearing in the limitations coiumn for this IR site are not limitations, but rather action levels. Whenever an action level is exceeded the shipyard shall inform the Department in writing within one week of becoming aware of such exceedance, and shall briefly describe its plans for preventing such exceedances in the future. IR sampling results shall not be reported on monthly _DMRs, but rather, in an annual report to the Department due March 1 5 of each. year.

-001 Co	nstruction	Dewatering	at	Installation
1 OW				
N/A	25,000	1/20,000		meter/tank
		gallon		
1,.3	1.3 1/2	0,000		grab
		gallon		C
3.2	3.2 1/2	U		grab
		· /		8
		8		
5	5 1/2	20.000		grab
-	-,-	,		8-11-
N/A	2.13	1/20 000		grab
1 1/11	2.13	20,000		gallon
	1 OW N/A 1,.3	1 OW N/A 25,000 1,.3 1.3 1/2 3.2 3.2 1/2 5 5 1/2	1 OW N/A 25,000 1/20,000 gallon 1,.3 1.3 1/20,000 gallon 3.2 3.2 1/20,000 gallon 5 5 1/20,000	N/A 25,000 1/20,000 gallon 1,.3 1.3 1/20,000 gallon 3.2 3.2 1/20,000 gallon 5 5 1/20,000

note:sampling is not required if less than 1000 gpd or 10,000 gallons per project
Numbers appearing in the limitations column for this IR site are not limitations, but rather action levels.
Whenever an action level is exceeded the shipyard shall inform the Department in writing within one week of becoming aware of such exceedance, and shall briefly describe its plans for preventing. such exceedances in the future. IR sampling results shall not be reported on monthly DMRs,but rather, in an annual report to the Department due March 15 of each year.

195 CO-IR1 1-001 Construction Dewatering at Installation Restoration Site 1 1 -

non steam sparging

Flow(gpd) N/A 43,200 1/20,000 meter/tank gallon TPH(G&D)(m N/A 1/20,000 200 g/L) gallon TTO's(mg/L) 2.13 1/20,000 2.13 grab gallon

note:sampli ng is not required if less than 1 000 gpd or 1 0,000 gallons per project Numbers appearing in the limitations column for this IR site are not limitations, but rather action levels.

Whenever an action level is exceeded the shipyard shall inform the Department in writing within one week of becoming aware of such exceedance, and shall- briefly describe its plans for preventing such exceedances in the future. IR sampling results shall not be reported on monthly DMRs, but rather, in an annual report to the Department due March 1 5 of each year.

N/A

1 96 CD-IR1 1 -001 S Steam Sparging Construction Dewatering at Installation

Restoration Site 1 1

Flow(gpd) N/A 43,200 N/A

Although listed here, this discharge is regulated under a separate agreement.

This discharge is not regulated in this permit.

197 CD-IR1 2-001 Construction Dewatering at Installation

Restoration Site 12

Ttobtorumon bitt			
Flow(gpd)	N/A	43,200 1/20,000	grab
	gallon		
Lead(mg/L)	1.3	1.3 1120,000	grab
	gallon		
Nickel(mg/L)	3.2	3.2 1/20,000	grab
, 0	gallon		C
Zinc(mg/L)	5	5 1/20,000	grab
()	gallon	,	C
TTO's(mg/L)	2.1 3	2.13 1/20.000	grab
	gallon	_,_,,,,,,	8-111
	Sanon		

note:sampling is not required if less than 1 000 gpd or 1 0,000 gallons per project

Numbers appearing in the limitations column for this IR site are not limitations, but rather action levels. Whenever an action level is exceeded the shipyard shall inform the Department in writing within one week of becoming aware of such exceedance,, and shall briefly describe its plans for preventing such exceedances in the future. IR sampling results shall not be reported on monthly DMRs, but rather, in an annual report to the Department due March 1 5 of each year.

198 Lift Station Municipal Lift Station

WB3

(West End)

Arsenic(mg/L) 0.1 5 0.1 5 monthly Composite

Lead(mg/L)	1.29	1.29 monthly	Composite
Mercury	0.09	0.09 monthly	Composite
Nickel(mg/L)	3.2	3.2 monthly	Composite
Zinc(mg/L)	5	5 monthly	Composite
Cyanide(T)(m	0.57	0.57 monthly	Composite
g/L)			
Salinity(SPSS)	N/A	N/A monthly	Composite

Note: The electrical conductivity method may be employed for determination of salinity note: SPSS is an index of salinity based on the practical salinity scale

199 first Street Lift	Municip	al Lift Station			
Station	ı (East	Arsenic(mg/L)	0.15	0. 1 5 m	onthly Composite
End)					
Cadmi	um(mg/	0.17	0.17	monthly,	Composite
L)					
Chrom	ium(mg	5	5 m	onthly	Composite
/L)					
Copper	(mg/L)	5.2	5.2	monthly	Composite
Lead(n	ng/L)	1.29	1.29	monthly	Composite
Mercui	. y	0.09	0.09	monthly	Composite
Nickel	(mg/L)	3.2	3.2	monthly	Composite
Zinc(m	ng/L)	5	5 m	onthly	Composite
Cyanid	le(T)(m	0.57	0.57	monthly	Composite
g/L)					
Salinit	y(SPSS	N/A	N/A	monthly	Composite

note: The electrical conductivity method may be employed for determination of salinity note: SPSS is an index of salinity based on the practical salinity scale